Aluminium

Window & Door Features



CASEMENT WINDOW RANGE



- Flush and Fully Flush design
- French Flush Casement window available
- Market-leading slim sightlines (61.5mm for flush and 75mm for fully flush)
- 1.4 W/m²K U-value (double glazed)
 1.0 W/m²K flush window (triple glazed)
 0.95 W/m²K fully flush (triple glazed)

- Espag locking
- Max size 1221mm x 1221mm (top hung) or 721mm x 1321mm (side hung)
- A++ rated WER band, unique thermal break technology
- Beads 28mm, 32mm, 36mm, 44mm (fully flush only)

FLUSH TILT & TURN WINDOW



- U-values as low as 1.4 W/m²K (double glazed) or 1.1 W/m²K (triple glazed)
- Contemporary slim sightlines
- Unique thermal break technology
- Concealed hardware for a sleek finish
- Extra security around hinge points
- Bead sizes: 28, 36, 44mm

FLUSH DOOR



- Fully Flush aesthetic
- 1.4 W/m²K (double glazed) or 1.2 W/m²K (triple glazed)
- Fully adjustable 3D hinge option
- Low profile DDA compliant threshold
- Max size 1000mm x 2400mm
- PAS 24 as standard
- Beads: 28, 32, 36, 44mm

UNIQUE SELLING POINTS

- · Unique and patented Reverse Butt Joint
- Fully internally beaded system with no need for reverse adaptors
- Knock-in beads
- Pre-gasketed system (incl. beads).
 Faster fabrication and installation

- Made in Britain
- Award-winning system
- Lifetime Security Guarantee with Yale hardware (Lift & Slide and Flush Tilt & Turn are not included)
- Contemporary square flush sightlines
- · PAS 24 as standard.

HARDWARE

- Hardware available in satin silver / white / black / chrome
- Yale Lifetime Security Guarantee

LIFT & SLIDE PATIO DOOR



- Three interlock options 96mm, 68mm or 50mm (windload dependent)
- Up to 44mm triple glazing
- 1.4 W/m²K U-value double glazed,
 0.9 W/m²K (triple glazed)
- Max panel weight 300kg / max size up to 3000mm x 3000mm
- PAS 24 as standard
- Beads: 28, 36, 44mm

SLIMLINE BIFOLD DOOR





- Robust hinge with double fixing positions
- Up to 44mm triple glazing
- Max panel weight 120kg / max size up to 1200mm x 2500mm
- PAS 24 as standard
- 117mm meeting style
- Patent-pending adjustable lock stile

- Beads: 28, 36, 44mm
- 1.3 W/m²K U-value (double glazed)
 / 0.9 W/m²K U-value (triple glazed)
- Unique thermal break technology



COLOURS / FINISHES

STOCK

 Qualicoat standard powder coating



Signal White Flat/Matt RAL 9003



Anthracite Grey Flat/Matt RAL 7016



Anthracite Grey/ Signal White Flat/Matt RAL 7016 / 9003



Jet Black Flat/Matt RAL 9005



Jet Black/ Signal White Flat/Matt RAL 9005 / 9003





Flat/Matt RAI 9001



Agate Grey Flat/Matt RAL 7038



Slate Grey Flat/Matt RAL 7015



Chocolate Bro Flat/Matt RAL 8017



Anthracite Grey Textured RAL 7016



Stafford Park 6, Telford TF3 3AT 0845 300 9356 talk@stellaraluminium.co.uk www.stellaraluminium.co.uk



Stellar Aluminium Systems is an aluminium profile system supplied to local independent manufacturers and installers who contract to install windows and doors. Stellar Aluminium cannot be held accountable for manufacture or installation by independent companies. All information in this publication is provided for guidance only and is given in good faith. As it is company policy to continually improve products, methods and materials, changes of specification may be made from time to time without prior notice. This statement does not affect your statutory rights.

© Stellar Aluminium Systems. Part of the Epwin Group Plc. STE17758